

22

27. The method of claim 25, wherein the step (c) includes a step of applying the recording layer on the reflection layer by spin coating---

layer.

the first base plate and the second base plate are bonded together via the adhesion an adhesion layer for bonding the second base plate to the first base plate, and

and

--11. The optical disc of claim 1, wherein the transparent member includes: a second base plate capable of transmitting the writing/reading radiation;

amended claims is attached hereto, having the bracketed additions and stricken deletions.

Please amend claims 11 and 27 to read as follows. A marked-up copy of the

Please amend the claims as follows:

In the Claims:

hereby amends the application as follows, without prejudice:

Preliminary Amendment is being filed, and prior to the calculation of the filing fee, Applicant simultaneously with the filing of the above-identified application with which this

PRELIMINARY AMENDMENT

For: OPTICAL DISC AND METHOD FOR MANUFACTURING THE OPTICAL DISC: (A1028MT-US1)
: Attorney Docket

Filed: Herewith

Appl. No.: Not Yet Assigned : Examiner:

Conf. No.: Not Yet Assigned

In Re: Patent Application of Shinya ABE *et al.* : Group Art Unit: Not Yet Assigned

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

EXPRESS MAILING LABEL NO.: EL916935354US

PATENT

5/a
MDS
3-20-03

105260-EEEEE9660